

PRODUCT INFORMATION SHEET

Masonry Cosmetic's Pigment Concentrate

masonry staining product



3210 Sugar Maple Business Court South
Bend IN 46628. (888) 698-8705 Fax: (574)
234-2240 www.masonrycosmetics.com
info@masonrycosmetics.com

FOR ALL SURFACES:

Create a test area by following the General Application Instructions. Additional coats can be applied if needed.

For Porous Surfaces:

Pigment will absorb quickly and drying time may vary between 5 and 10 minutes depending on outside temperature.

For Smooth Surfaces:

Pigment will not absorb as quickly and drying time may vary between 15 minutes and 2 hours depending on outside temperature.

Cold Weather Application

DO NOT apply pigment below 40° F or if the temperature is expected to drop below 32° within a 24-hour period. Do not apply if the surface temperature is below 40° F.

WARRANTY

Masonry Cosmetics Inc. warrants its unique and proprietary products to be of the highest quality that will not peel, fade, crack, blister or seal the surface. Since application of the product is crucial and beyond the control of Masonry Cosmetics Inc., no warranty will be made on self-application. A refund of the purchase price or replacement of product constitutes the limit of our liability. If we apply pigments, a Lifetime Warranty will be given on most projects (mortar not included).

PRODUCT DESCRIPTION:

Masonry Cosmetics Inc's Pigment Concentrate is a unique and proprietary stain that consists of mineral oxides that absorb into the pore structure of most masonry surfaces and then bonds with the surface, resulting in a transformation of the appearance of the masonry surface to another shade of color without sealing the surface or leaving a shine.

USAGE:

Brick
Mortar
Block
Cast Stone
Manufactured Stone
Natural Stone
Limestone
Concrete Pavers

APPLICATION:

General Applications Instructions:

Surfaces must be:

- "clean" - properly washed down and PH neutralized
- "dry" - fully cured
- "warm" - at a minimum temperature of 40° F or higher

STORAGE & HANDLING:

Store pigment in cool dry area.

APPLICATION:

1. Remove any coatings or substances that may prevent penetration of the pigment (e.g. sealers, dirt, surface oil, tar, paint)
2. Create a formula of color and add water. Stain a small test area and adjust colors as needed.
3. Apply with a brush
4. Wipe any run down with damp cloth
5. Complete drying is critical for the chemical bonding process to occur.
6. Additional applications can be added if needed to reach desired color.

DISPOSAL:

Dilute with water and dispose of away from concrete or asphalt to avoid staining surfaces. Continue to rinse with water until cup and brush runs clear. (Our products are environmentally friendly.)

MAINTENANCE & CLEANING

No Maintenance is needed. Any cleaning chemical should be limited to water and no pressure washing should be allowed.

Caution: Avoid contact with eyes. In case of contact, flush with plenty of water. In case of persistent irritation, contact a physician.